

Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name:

FOLBIT 800

Liquid foil

Relevant identified uses of the substance or mixture and uses advised against

Life cycle stages

C/PW Consumer use / Widespread use by professional workers

Sector of Use

SU19 Building and construction work

Product category

PC1 Adhesives, sealants

Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC19 Manual activities involving hand contact

Environmental release category

ERC10a / ERC11a Widespread use of articles with low release

Article category

AC0 Other

Application of the substance / the preparation

Sealant - Product for an industrial, technical and private use for processing on buildings. For all other uses is advised against/ not recommended.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KREISEL - Technika Budowlana Sp. z o.o. ul. Szarych Szeregów 23 60-462 Poznań Poland

Tel. +48 61 846 79 00 Fax +48 61 846 79 09 sekretariat@kreisel.pl www.kreisel.pl

Further information obtainable from:

Bartosz Polaczyk - Tel.: +48 510 022 908, +48 61 84 67 966, bartosz.polaczyk@kreisel.pl On working days 8 a.m. - 4 p.m.

Emergency telephone number



National poisons information centre: +44/(0)171 - 635 9191

National Health Service: 111 European emergency call: 112

GB



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 1)

SECTION 2: Hazards identification

Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

Label elements

GHS label elements Void

Hazard pictograms

Void

Signal word

Void

Hazard statements

Void

Additional information:

EUH208 Contains 1,2-Benzisothiazol-3(2H)-one, 2-Methyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Other hazards

No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

Chemical characterization: Substances

This product is a mixture.

Mixtures

Description:

Mixture of acrylat dispersion and fillers with nonhazardous additions.

Dangerous components:		
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 REACH: 01-2119489379-17	Titanium dioxide (<1% particles ≤ 10µm, Note 10)	1 - 2.5%
EINECS: 220-120-9 Index number: 613-088-00-6 REACH: 01-2120761540-60	1,2-Benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥0.05 %	< 0.03%
EINECS: 220-239-6 REACH: 01-2120764690-50	2-Methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥0.0015 %	< 0.0015%

(Contd. on page 3)



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 2) Other components (>20%): CAS: 7732-18-5 Water 25 - 50% EINECS: 231-791-2 REACH: 1 CAS: 1317-65-3 Limestone (Calcium carbonate) 25 - 50% EINECS: 215-279-6 Consisting of: 471-34-1 Calcium carbonate (> 90%); 16389-88-REACH: 1 1 Calcium/Magesium carbonate (0 - 10%); 14808-60-7 Quartz (SiO₂) (0 - 10%); 37244-96-5 Feldspar (0 - 5%); 12001-26-2 Mica - Potassium aluminum silicate (Muscovite) (0 - 5%) EC number: 920-793-5 Styrene acrylates copolymer 25 - 50% REACH: 1

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m.

SECTION 4: First aid measures

Description of first aid measures



First aid

General information:

For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

After inhalation:

Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contamionated shoes before reuse. If skin irritation continues, consult a doctor.

After eye contact:

Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

After swallowing:

Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control center.

Most important symptoms and effects, both acute and delayed

Symptoms and effects are described in section 2 and 11.

Hazards:

No further relevant information available.

(Contd. on page 4)

¹ Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 3)

Indication of any immediate medical attention and special treatment needed

If a physician is to be consulted, as per possibillity he should be presented this safety data sheet.

SECTION 5: Firefighting measures

Extinguishing media

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

Suitable extinguishing agents:

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

Special hazards arising from the substance or mixture

This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

Advice for firefighters

No special measures required. Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

If appropriate, reference must be made to exposure controls and personal protection (see section 8).

Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

Information about fire - and explosion protection:

No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

(Contd. on page 5)



Printing date 12.02.2024 Version number: RO/ 3 (replaces version 2) Revision: 02.02.2024

FOLBIT 800

(Contd. of page 4)

Information about storage in one common storage facility:

Keep away from foodstuffs, beverages and feed.

Further information about storage conditions:

Protect from frost. Protect from heat and direct sunlight.

Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Storage class: 12 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Outlier parameters	Control	parameters
--------------------	---------	------------

Ingredients with limit values that require monitoring at the workplace:	
13463-67-7 Titanium dioxide (<1% particles ≤ 10μm, Note 10)	
WEL (Great Britain)	Long-term value: 10* 4** mg/m³ *total inhalable **respirable
DNELs	
13463-67-7 Titaniui	n dioxide (<1% particles ≤ 10μm, Note 10)

13463-67-	/ litanium dioxide (<1% partic	eies ≤ 10µm, Note 10)
Oral	Long term exposure	700 mg/kg bw/d (Consumer)
Inhalative	Systemic - Long term exposure	10 mg/m³ (Employee)
2634-33-5	1,2-Benzisothiazol-3(2H)-one	
Dermal	Systemic - Long term exposure	0.345 mg/kg bw/d (Consumer)
		0.966 mg/kg bw/d (Employee)
Inhalative	Systemic - Long term exposure	1.2 mg/m³ (Consumer)
		6.81 mg/m³ (Employee)
2682-20-4	2-Methyl-2H-isothiazol-3-one	
Oral	Long term exposure	0.027 mg/kg bw/d (Consumer)
	Short term exposure	0.053 mg/kg bw/d (Consumer)
Inhalative	Local - Long term exposure	0.021 mg/m³ (Consumer)
		0.021 mg/m³ (Employee)
	Local - Short term exposure	0.34 mg/m³ (Consumer)
		I I

		, , ,
2682-20-4	2-Methyl-2H-isothiazol-3-one	
Oral	Long term exposure	0.027 mg/kg bw/d (Consumer)
	Short term exposure	0.053 mg/kg bw/d (Consumer)
Inhalative	Local - Long term exposure	0.021 mg/m³ (Consumer)
		0.021 mg/m³ (Employee)
	Local - Short term exposure	0.34 mg/m³ (Consumer)
		0.34 mg/m³ (Employee)
PNFCs		

I NEO3	
13463-67-7 Titanium dioxide (<1% particles < 10um, N	lote 10)

Freshwater	0.127 mg/l
Marine water	1 mg/l
Soil	> 100 mg/kg
Sediments (Freshwater)	> 1,000 mg/kg
Sediments (Marine water)	
Sewage plant	100 mg/l

2634-33-5 1,2-Benzisothiazol-3(2H)-one

Freshwater	0.00403 mg/l (not specified)
Marine water	0.000403 mg/l (not specified)
Soil	3 mg/kg (not specified)
Sediments (Freshwater)	0.0499 mg/kg (not specified)

(Contd. on page 6)



Printing date 12.02.2024 Version number: RO/ 3 (replaces version 2) Revision: 02.02.2024

FOLBIT 800

	(Contd. of page 5)
Sediments (Marine water)	0.000499 mg/kg (not specified)
Sewage plant	1.03 mg/l (not specified)
2682-20-4 2-Methyl-2H-is	othiazol-3-one
Freshwater	0.00339 mg/l (not specified)
Soil	0.047 mg/kg (not specified)
Sediments (Marine water)	0.00339 mg/kg (not specified)
Sewage plant	0.23 mg/l (not specified)

Ingredients with biological limit values:

Void

Additional information:

The lists valid during the making were used as basis.

Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the work place.

Respiratory protection:



Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

Hand protection:



Hand protection: Chemical resistant protective gloves according EN ISO 374

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skin-protecting agents is recommended. To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Polychloroprene (material thickness $\geq 0.5 \ mm$; breakthrough time $\geq 480 \ min.$)

Nitrile rubber (material thickness ≥ 0.35 mm; breakthrough time ≥ 480 min.)

Butyl rubber (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.)

Fluororubber (material thickness ≥ 0.4 mm; breakthrough time ≥ 480 min.)

Neoprene (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.)

(Contd. on page 7)



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 6)

Not suitable are gloves made of the following materials:

Non-liquid-tight gloves made of fabric, leather or similar materials.

Eye/face protection:



In case of splash risk use tightly fitting safety goggles according to EN 166.

Body protection:



Protective work clothing

Risk management measures:

An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

Information about design of technical facilities

No further data; see item 7.

Environmental exposure controls

Avoid release in the environment. Use the surplus or dispose it of properly.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

General Information

Physical state Fluid

Appearance:

Form: Pasty
Colour: Light blue
Odour: Mild

Odour threshold: Not safety relevant

pH at 20 °C (68 °F) 8 - 10

Saturated aqueous solution

Change in condition

Melting point/freezing point: $\sim 0 \, ^{\circ}\text{C} \, (\sim 32 \, ^{\circ}\text{F}) \, (\text{ISO } 3016)$

Boiling point or initial boiling point and

boiling range 100 °C (212 °F)

Flammability Product is not flammable.

Flash point: Not applicable

Auto-ignition temperature: $> 400 \,^{\circ}\text{C} \, (> 752 \,^{\circ}\text{F}) \, (DIN \, 51794)$

Decomposition temperature: > 825°C to CaO and CO₂

Oxidising properties: None

Explosive properties: Product does not present an explosion hazard.

Lower and upper explosion limit

Lower: Not determined Upper: Not determined

Ignition temperature: Product is not selfigniting. **Vapour pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

Density and/or relative density

Density at 20 °C (68 °F): 1.4 - 1.6 g/cm³ (11.68 - 13.35 lbs/gal)

(Contd. on page 8)



Printing date 12.02.2024 Version number: RO/ 3 (replaces version 2) Revision: 02.02.2024

FOLBIT 800

(Contd. of page 7)

Particle size Viscosity:

Dynamic at 20 °C (68 °F): > 1,000 mPas (DIN 53019)

Solubility

Water: Not miscible or difficult to mix

Solids content: 60 - 64 %

Solvent content:

Organic solvents: 0.5 %

 VOC without water (EC):
 15.65 - 21.66 g/l

 VOC with water (EC):
 7.06 - 8.07 g/l

 VOC with water (EC):
 0.504 %

Other information

Information with regard to physical hazard

classes **Explosives** Void Void Flammable gases **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void Self-heating substances and mixtures Void

Self-heating substances and mixtures
Substances and mixtures, which emit
flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Void
Desensitised explosives
Void

SECTION 10: Stability and reactivity

Reactivity

No dangerous reactions known.

Chemical stability:

The product is stable as long as it is stored properly and dry.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions

No dangerous reactions known.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

Hazardous decomposition products

No dangerous decomposition products known.

(Contd. on page 9)



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 8)

Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Additional information:

No further relevant information available.

SECTION 11: Toxicological information

Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product was not investigated. The statement is derivated from the properties of the single components.

Acute toxicity:

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
1317-65-3	1317-65-3 Limestone (Calcium carbonate)		
Oral	Oral LD ₅₀ 6,450 mg/kg (Rat) (RTECS Data)		
Styrene a	crylates copoly	mer	
Oral	LD ₅₀	> 5,000 mg/kg (Rat)	
Dermal	LD ₅₀	> 5,000 mg/kg (Rat)	
13463-67-	7 Titanium diox	ide (<1% particles ≤ 10µm, Note 10)	
Oral	LD ₅₀	> 5,000 mg/kg (Rat) (OECD 425)	
	Carcinogenicity	(Mouse) (ECHA Registration dossier) no effects observed	
Dermal	LD ₅₀	> 5,000 mg/kg (Rabbit)	
2634-33-5 1,2-Benzisothiazol-3(2H)-one			
Oral	LD ₅₀	1,150 mg/kg (Mouse)	
		597 mg/kg (Rat)	
Dermal	LD ₅₀	> 2,000 mg/kg (Rat)	
2682-20-4	2682-20-4 2-Methyl-2H-isothiazol-3-one		
Oral	LD ₅₀	232 - 249 mg/kg (Rat) (OECD 401)	
Dermal	LD ₅₀	242 mg/kg (Rat) (OECD 402)	
Inhalative	LC ₅₀ (4h)	0.05 mg/l (ATE)	
	LC ₅₀ (4h)	0.11 mg/l (Rat) (OECD 403)	

Other information (about experimental toxicology):			
13463-67-7 Titanium dioxide (<1% particles ≤ 10μm, Note 10)			
Oral	OECD 414 (Prenatal Developmental Toxicity)	(Rat) no effects observed	
Irritation of skin	OECD 404 (skin)	(Rabbit) not corrosive	
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant	
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing	
	OECD 421 (Reproduction screening test)	(Rat) no effects observed	
2682-20-4 2-Methyl-2H-isothiazol-3-one			
Oral	OECD 408 (Repeated dose oral toxicity 90d)	19 mg/kg bw/day (Rat)	
	ı	(Contd. on page 10)	

(Contd. on page 10



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 9) Irritation of skin OECD 404 (skin) (Rabbit) corrosive Sensitisation OECD 406 (sensitization) (Guinea pig) sensitizing

On the skin:

Based on available data, the classification criteria are not met.

On the eye:

Based on available data, the classification criteria are not met.

Sensitization:

Sensitising effect by skin contact is possible by prolonged exposure.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure (STOT SE):

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure (STOT RE):

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Practical experience

No further relevant information available.

General comments

No further relevant information available.

Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

Toxicity

The product was not investigated. The statement is derivated from the properties of the single components.

Aquatic toxicity:		
1317-65-3 Limestone (Calcium carbonate)		
LC ₅₀ (96h)	> 100 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)	
LC ₅₀ (48h)	> 100 mg/l (Water flea - daphnia magma) (OECD 202)	
EC ₅₀	> 14 mg/l (Algae - desmodesmus subspicatus) (OECD 201)	
	> 1,000 mg/l (Activated sewage sludge) (OECD 209)	
Styrene acrylates copolymer		
LC ₅₀ (96h)	> 100 mg/l (Zebrafish - danio rerio)	
EC ₅₀ (48h)	> 100 mg/l (Water flea - daphnia magma)	
EC ₅₀ (72h)	> 100 mg/l (Algae - desmodesmus subspicatus)	
	(Contd. on page	



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

	(Contd. of pag			
13463-67-7 Titanium dioxide (<1% particles ≤ 10μm, Note 10)				
LC ₅₀ (48h)	5.5 mg/l (Water flea - daphnia magma)			
LC₅₀ (96h Marine water)	> 10,000 mg/l (Fish)			
LC₅₀ (96h Freshwater) (stati	c) > 100 mg/l (Goldfish) (OECD 203)			
EC ₅₀ (48h)	> 1,000 mg/l (Water flea - daphnia magma) (ASTM Standard E72			
EC ₅₀ (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)			
EC ₅₀ (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)			
EC ₅₀ (7d)	> 100 mg/l (Lemna minor) (OECD 221)			
NOEC (48h)	1 mg/l (Water flea - daphnia magma)			
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magma) (OECD 202)			
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219) Soil			
NOEC (32d)	> 1 mg/l (Scenedesmus quadricauda)			
NOEC (8d)	> 1,000 mg/l (Zebrafish - danio rerio) (OECD 212)			
2634-33-5 1,2-Benzisothia	zol-3(2H)-one			
LC ₅₀ (96h)	1.6 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)			
EC ₅₀ (48h)	3.27 mg/l (Water flea - daphnia magma)			
	1.5 mg/l (Water flea - daphnia)			
EC₅₀ (72h)	0.11 mg/l (Algae - selenastrum capricornutum) (OECD 201)			
	2 mg/l (Algae scenedesmus subcapitatus)			
EC ₅₀ (16h)	0.4 mg/l (Pseudomonas putida)			
EC ₁₀ (72h)	0.04 mg/l (Algae - selenastrum capricornutum) (OECD 201)			
NOEC (21d)	1.2 mg/l (Water flea - daphnia magma) (OECD 202)			
NOEC (28d)	0.21 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 215)			
2682-20-4 2-Methyl-2H-iso	thiazol-3-one			
LC ₅₀ (96h Marine water)	2.98 mg/l (Water flea - daphnia magma)			
LC₅₀ (96h Freshwater)	0.934 mg/l (Water flea - daphnia magma)			
LC ₅₀	4.77 mg/l (Fish) (OECD 203)			
EC ₁₀	0.044 mg/l (Water flea - daphnia magma) (OECD 211)			
	4.93 mg/l (Fish)			
EC ₅₀	41 mg/l (Activated sewage sludge) (OECD 209)			
	0.103 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201			
EC ₅₀ (16h)	2.3 mg/l (Pseudomonas putida)			

Persistence and degradability
A part of the components is biodegradable.

Degree of elimination:		
2634-33-5 1,2-E	Benzisothiazol-3(2H)-one	
Biodegradation	> 70 % (Activated sewage sludge) (OECD 303 A)	
	> 90 % (not specified) (OECD 302 B)	
Bioaccumulati	ve potential	
2634-33-5 1,2-E	Benzisothiazol-3(2H)-one	
Log Kow 0.7 (n	ot specified) (OECD 117)	
Bioconcentrati	ion factor (BCF)	
2634-33-5 1,2-E	Benzisothiazol-3(2H)-one	
Bioconcentratio	n factor (BCF) 6.95 (not specified) (OECD 305)	
	(Contd. on pa	ge



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 11)

Mobility in soil

No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

Other adverse effects

No further relevant information available.

Literature

No further relevant information available.

Ecotoxical effects:

No further relevant information available.

Behaviour in sewage processing plants:				
Styrene acrylates copolymer				
EC ₂₀ (0,5h)	> 100 mg/l (Activated sludge organisms)			
2634-33-5 1,2-Benzisothiazol-3(2H)-one				
EC ₂₀ (0,5h)	3.3 mg/l (Activated sludge organisms) (OECD 209)			
EC ₂₀ (3h)	3.3 mg/l (Activated sludge organisms) (OECD 209)			
EC ₅₀ (3h)	13 mg/l (Activated sludge organisms) (OECD 209)			
OECD 302 B Zahn Wellens Test	90 % (Activated sludge organisms) (OECD 302)			
OECD 303 A Activated Sludge Units	l Sludge Units % (Rat)			
	> 70 % (Activated sludge organisms) (OECD 303 A)			
2682-20-4 2-Methyl-2H-isothiazol-3-one				
EC ₂₀ (3h)	2.8 mg/l (Activated sludge organisms) (DIN 38412-3 TTC-Test)			

Additional ecological information:

General notes:

Not hazardous for water.

SECTION 13: Disposal considerations

Waste treatment methods

Recommendation:





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container in accordance with local/regional/national/international regulations.

17 09 04 for the setted product

08 01 20 for residues of the unprocessed product

15 01 02 for the completely emptied packaging

(Contd. on page 13)



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 12)

Uncleaned packaging

Recommendation:

Disposal must be made according to official regulations.

Recycle only completely emptied packaging.

UN number or ID number ADR, ADN, IMDG, IATA	Void
UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
Packing group ADR, IMDG, IATA	Void
Environmental hazards Marine pollutant:	No
Special precautions for user	Not applicable
Maritime transport in bulk according instruments	y to IMO Not applicable
UN "Model Regulation":	Void

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act				
Regulated explosives precursors				
None of the ingredients is listed.				
Regulated poisons				
None of the ingredients is listed.				
Reportable explosives precursors				
7631-99-4 Sodium nitrate	Listed			
Reportable poisons				
1310-73-2 Sodium hydroxide	12% of total caustic alkalinity			
50-00-0 Formaldehyde	5%			
OHO lab al alama mta Vicil	·			

GHS label elements Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Directive (EU) 2012/18

Named dangerous substances - ANNEX I:

None of the ingredients is listed.

(Contd. on page 14)



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 13)

Biozide ingredients (528/2012/EG):

Data based on recipe and information on the raw materials from the supply chain.

1,2-Benzisothiazol-3(2H)-one	< 0.03%
Tetramethylolacetylene diurea	< 0.03%
2-Methyl-2H-isothiazol-3-one	< 0.0015%

Classification according 2004/42/EG:

IIA(c) 40 - this product contains < 40 g/I VOC (see chapter 9)

Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Reasons for changes:

* Data compared to the previous version altered.

Relevant phrases:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

Advice for instructions:

Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

Literature and the data sources:

Department issuing MSDS:

Product safety department (+43/(0)5522-41646-0 / klaus.ritter@fixit-gruppe.com)

Contact:

Dr. Klaus Ritter

Date of previous version: 26.05.2023 Version number of previous version: 2

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/Germany)

PBT: persistent, bioaccumulative and toxic properties

vPvB: very persistent, bioaccumulatice properties

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 15)



Revision: 02.02.2024

Printing date 12.02.2024

Version number: RO/ 3 (replaces version 2)

FOLBIT 800

(Contd. of page 14)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Further information:

The information in this safety data sheet describe the safety requirements of our product and is based on our current state of our knowledge. They provide no assurance of product quality. Existing laws, ordinances and regulations, including those that are not mentioned in this data sheet must be observed by the recipient of our products in their own responsibility.

GB