



ACRYLIC AZURE 1003


Colourful finishing of FACADE BOARD

Areas of application: Primer intended for final preparation of concrete surfaces before the application of gypsum and cement-lime plasters
Intended for decorative, colourful finishing of surface of profiles imitating wooden strips.
After drying, it creates a seamless, durable, flexible insulation coating.

- Properties:**
- Easy to process
 - Rich color palette
 - Resistant to overgrowth
 - UV-resistant
 - Water-repellent
 - Environmentally friendly

Application procedure:



Technical data	
Item no.	-
Packaging type	
Quantity per unit	2.5 l 5 l
Unit per pallet	100 Pcs/pallet 80 Pcs/pallet
Colour	coloured
Consumption	approx. 0.15 l/m ²
Drying time	About 12h (one layer)
Hardening time	approx. 24 h

- Material base:**
- Special acrylic polymer dispersion
 - Additives
 - Pigments
 - Water

Surface: Eradicate all expressions of biological aggression using the SEPTOBUD 1008 solution or grind groundwork mechanically.
Cover all surfaces which are not intended for painting or finishing with mortar.

Types of substrate: **DECORATIVE FACADE BOARD:** Apply directly
Thin-layer mineral and dispersion plasters: Apply directly

Preparation: Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use.
Before applying, check if the color matches your order.

Application procedure: Apply the paint with a roller, brush or using a spray-application unit
To achieve the rustic effect, directly after painting, the fresh scumble shall be wiped delicately with a clean, dry sponge
Can be applied in two layers. The second layer deepens the colour

Application conditions: Apply in temperatures from +5 °C to +25 °C, these temperature refer to air, groundwork and product temperature.

Instructions: Protect against precipitation, excessive sun rays, wind and frost during application and drying
The use of scaffolding covers is recommended

Storage: Maximally 12 months
In dry areas and in non-damaged factory packaging, at temperatures from +5 °C to +25 °C.



ACRYLIC AZURE 1003

Colourful finishing of FACADE BOARD

General information:

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.