



SEPTOBUD 1008

Biocide

Areas of application: Intended for removing microorganisms (algae, mold) on facades, plasters, etc. Also suitable for cleaning, disinfecting walls roofs, rustproof production devices, sanitary equipment, etc.
Indoor and outdoor use

Properties:

- Easy to use
- Effective

Application procedure:



Technical data	
Item no.	10615
Packaging type	
Quantity per unit	1 l
Unit per pallet	12 Pcs/carton
Colour	colorless
Density	approx. 1 g/cm ³
Consumption	0.1 l/m ²
pH-value	approx. 5.5

Material base:

- Water
- Active ingredients: didecyldimethylammonium chloride, 2-octyl-2H-isothiazol-3-one
- Additives

Preparation: Ready-to-use product. Do not dilute
Do not add water or any other solutions, e.g. dyes or surfactants. Do not mix with dry or wet construction chemistry products. Protect against washing by precipitation.

Application procedure: Apply the product with a brush, roller or a machine-spray unit on the infected surface. Leave for 24 hours to eradicate the microorganisms, then wash, e.g. with a pressure washer. High-humidity weather facilitates the action of solution components. Rain, however, is undesirable (washes the solution off the surface).
When disinfecting chemical tanks, production systems, spray the entire surface thoroughly and leave for 24 hours to dry. After this time, wash thoroughly.
Remove deactivated microorganisms on walls and roofs with a sharp brush or water pressure device. In order to completely remove biological aggression, it is recommended to use the product again. After re-application, wait a minimum of 24 hours. Only after this time can you prime, paint and apply plasters. Microorganisms must not be removed before using the preparation as this leads to their spread.

Application conditions: Apply in temperatures from +5 °C to +25 °C, these temperature refer to air, groundwork and product temperature.

Instructions: Do not add Septobud to paints, primers, etc.

Storage: The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.

General information: The mold eradicating solution is harmful to health. Avoid skin and eye contact during use. Keep away from children. Observe the guidelines on the packaging and on the material safety data sheet.