



ANTI condensation plaster 025

Special plaster for wet rooms

Areas of application: After drying, the grout creates a flexible, mold-resistant and durable plaster layer. Plaster with a structure of 2mm is also suitable for mechanical use.

Properties:

- Absorbs moisture
- Indoor use
- White
- Flexible
- Waterproof

Application procedure:

Technical data					
Item no.				427314	37968
Packaging type					
Quantity per unit	25 kg				
Unit per pallet	33 Pcs/pallet				
Colour	White				
Plaster structure	pitted	pitted	pitted	Dashed	Dashed
Granulation	0 - 1.5 mm	0 - 2 mm	0 - 3 mm	0 - 0.5 mm	0 - 1 mm
Consumption	1.2 kg/m ²	2.4 kg/m ²	3.7 kg/m ²	2 kg/m ²	1.6 kg/m ²
Drying time	from 24 to 48 hours				
Application time	max. 20 min				

Item no.	37967	37966	37964
Packaging type			
Quantity per unit	25 kg		
Unit per pallet	33 Pcs/pallet		
Colour	White		
Plaster structure	Dashed		
Granulation	0 - 1.5 mm	0 - 2 mm	0 - 3 mm
Consumption	2.4 kg/m ²	3.5 kg/m ²	5 kg/m ²
Drying time	from 24 to 48 hours		
Application time	max. 20 min		

Material base:

- Mineral fillers
- Polymers
- Additives

Surface: Prime the groundwork with TYNKOLIT-U 340 at minimum 24 hours before the application of plaster. Symptoms of biological aggression should be eliminated. Prior to applying TYNKOLIT-SO 332, prime very absorbent groundworks with GRUNTOLIT-W 301.

Preparation: Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use.

Application procedure: Apply the plaster on the substrate with a trowel of stainless steel to be as thick as a grain, afterwards - excess must be removed with the same trowel. Finally, rub with a trowel of plastic.



ANTI condensation plaster 025

Special plaster for wet rooms

Application conditions:	Apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.
Instructions:	One one surface, apply plaster from one production batch only. Process a surface in a continuous manner, applying the „wet on wet“ method to avoid visible lines. Clean tools with clean water immediately after finishing work. The product has the ability to condense 190 g of water / 1 m ² of surface
Storage:	Up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C, far from sources of heat and frost.
General information:	This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing. All technical data is given for the temperature of 20 degrees Celsius. These temperatures apply to air, bed and embedded material.