



ROLTYNK 070

Mineral decorative render

Areas of application: Mortar on the basis of cement, intended for manual execution of decorative, thin-layer plaster layers.
Depending on the tools used, different modeling of plaster is possible, as well as achievement of diverse, original textures is possible too. Based on this mass you can make an imitation of facade plank using matrixes for impressing a model of wood. Based on the product, you can achieve the effect of smooth and even facade.
Indoor and outdoor use

Properties:

- fine-grained
- For imitation bricks and boards
- Vapor-permeable
- High grip
- UV-resistant
- Frost-resistant
- Waterproof

Application procedure:



Technical data	
Item no.	30057
Packaging type	
Quantity per unit	25 kg
Unit per pallet	48 Pcs/pallet
Colour	White
Granulation	0 - 0.5 mm
Consumption	approx. 1.5 g/m ²
Drying time	from 24 to 48 hours
Application time	approx. 20 min
Layer thickness	2 - 5 mm
Soluble chromium VI content	≤ 0.0002 %
Amount of water required	approx. 6.9 l/bag
Water vapour permeability	V2 - medium
Adhesion to	≥ 0.3 MPa

The product conforms to: • EN 15824

Material base:

- White Portland cement
- Hydrated lime
- Mineral fillers
- Additives

Surface: Before applying the plaster, all groundworks must be primed with TYNKOLIT-T 330
Symptoms of biological aggression should be eliminated.
Prior to applying TYNKOLIT-T 330, prime very absorbent groundworks with GRUNTOLIT-W 301

Types of substrate:

Reinforcing layer in the thermal insulation system: Prime with TYNKOLIT-T 330 or TYNKOLIT 340

Cement-lime plaster: Prime with TYNKOLIT-T 330 or TYNKOLIT 340

Gipsputz: Prime with TYNKOLIT-T 330 or TYNKOLIT 340

Gypsum plasterboards: Prime with TYNKOLIT-T 330 or TYNKOLIT 340

Concrete, reinforced concrete: Prime with TYNKOLIT-T 330 or TYNKOLIT 340



ROLTYNK 070

Mineral decorative render

Preparation:	<p>Pour the dry mix gradually to a container with a sufficient amount of clean, cool water, mixing manually or using a low-speed mixer to produce homogenous, lump-free mass. Leave to mature for 5 minutes, and then mix again.</p> <p>To avoid color differences, prepare each consecutive batch in the same manner, using an identical amount of water.</p>
Application procedure:	<p>Apply the plaster using a stainless steel long float, maintaining the desired thickness, depending on the adopted modeling method and anticipated outcome. Process with a long float or another tool directly after applying the plaster.</p> <p>While performing works and during drying process, protect from frost, rainfalls, too high temperatures and strong winds.</p> <p>The use of scaffolding covers is recommended</p>
Application conditions:	<p>Apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean</p> <p>Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.</p>
Instructions:	<p>One one surface, apply plaster from one production batch only.</p> <p>Process a surface in a continuous manner, applying the „wet on wet“ method to avoid visible lines. Organize works to make sure the processing method is compatible with the plaster drying time, producing a uniform, desired effect on the entire surface.</p> <p>After drying, coat the plaster with a single layer of equalizing paint in the desired color.</p>
Storage:	<p>Up to 12 months from the date of manufacture, in dry places and in intact packaging</p>
General information:	<p>This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.</p>